

FRESH WATER

TP 36 EX
Pumps Range

Self-Priming

ENGINE
4ST | Gasoline

DISCHARGE FLOW
31.2 m³/h

PRESSURE
3.2 bar

SOLID SIZE Ø
5.5 mm

NET WEIGHT
25 kg



3 YEARS
WARRANTY



TP range are suitable for clear and light trash transfer and accept particles up to 7.5 mm. High-performance materials such as the ceramic carbon mechanical seal and die-cast aluminum body pump provide excellent reliability and durability.

Standard equipment

- ✓ Four-stroke OHC engine
- ✓ Recoil start
- ✓ Electronic oil sensor security
- ✓ Ceramic carbon mechanical seal
- ✓ Plastic strainer, hose coupling and clamp

Optional equipment

- + Wheelbarrow kit (factory option): REF. 13
- + Firefighter hose coupling
- + Maintenance KIT N°2

TP 36 EX		
Pump type		Self-Priming
Suction Ø coupling	mm	50 (2")
Delivery Ø coupling	mm	50 (2")
Discharge flow	L/min	520
Discharge flow	m ³ /h	31.2
Pressure	bar	3.2
Total dynamic head	m	32
Discharge head	m	8
Solid size Ø (Ø of strainer holes)	mm	5.5
Mechanical seal		Ceramic carbon
Engine model		WORMS EX16
Engine type		OHC, 4-stroke gasoline
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	3.2
Autonomy	h	3 h
Dimensions L x l x H	mm	527 x 368 x 417
Packaging dimensions L x W x H	mm	545 x 380 x 430
Net Weight	kg	25
Gross weight	kg	27

WORMS Entreprises

ZAC de Lamirault
39 rue de Lamirault
77090 Collégien
FRANCE
TEL. +33 (0) 1 64 76 29 50
FAX +33 (0) 1 64 76 29 99
www.wormsentreprises.com